```
ANSWER 1 OF 4 CA COPYRIGHT 2004 ACS on STN
L3
     135:9088 CA
AN
     Entered STN: 21 Jun 2001
ED
     Method and apparatus for producing lightweight cellular concrete
ΤI
IN
     Etherton, Philip
     Innovation Holding (U.K.) Limited, UK
PΑ
     Eur. Pat. Appl., 13 pp.
SO
     CODEN: EPXXDW
DT
     Patent
     English
LA
IC
     ICM C04B038-10
     ICS C04B028-02; E01C007-14; E01C019-02; B28C005-38; B28C009-04;
          B28C007-06
     58-2 (Cement, Concrete, and Related Building Materials)
CC
FAN.CNT 1
                                          APPLICATION NO.
                                                                   DATE
                                DATE
     PATENT NO.
                         KIND
                                            ______
                                -----
                         _ _ _ _
                                           EP 2000-310537
                                                                   20001128
                                20010530
     EP 1103533
                         A2
PI
                                20010801
     EP 1103533
                         Α3
         R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT,
             IE, SI, LT, LV, FI, RO
                                           GB 1999-28168
                                                                   19991129
     GB 2356628
                          Α1
                                20010530
     GB 2356628
                          B2
                                20040428
PRAI GB 1999-28168
                          Α
                                19991129
CLASS
                CLASS PATENT FAMILY CLASSIFICATION CODES
 PATENT NO.
                        ______
                ----
 EP 1103533
                 ICM
                        C04B038-10
                        C04B028-02; E01C007-14; E01C019-02; B28C005-38;
                 ICS
                        B28C009-04; B28C007-06
                        B01F005/04C14B; B01F005/04C14C; B01F007/08C;
 EP 1103533
                ECLA
                        B28C005/12F2; B28C005/12F4; B28C005/38B; B28C007/00A2;
                        B28C007/6; B28C009/04F; B28C009/04F2; C04B028/02;
                        C04B038/10; C04B040/00D; E01C011/00B; E01C019/02B
                        B28C005/38B; B28C007/06; B28C009/04F; C04B028/02;
 GB 2356628
                 ECLA
                        C04B038/10; E01C011/00B; E01C019/02B
     A process and app. are designated to manuf. a low d. foam concrete
AB
     contg. a recycled, excavated materials. The excavated materials are
     crushed, graded and used in a ratio of 6:1 with the cement with
     a foaming agent (esp. Zenfoam - a blend of hydrolyzed
    protein and surfactants). A preformed foam may be used
to obtain a high void vol. and a plasticizer (esp. Zenplus) added to
     improve fluidity. The foam concrete is manufd. on-site on a
     continuous basis using a mobile concrete making vehicle having
     an elongate tubular mixer into which the components are introduced at
     selected points along its length, to control the final compn. of the mix.
     The mixer has internal agitating means that cause backflow to enable the
     concrete to be dispensed directly at ground level.
ST
     cellular lightwt concrete cement excavated clay
```

TT

Concrete